

Vertex S

BACKSHEET MONOCRYSTALLINE MODULE

PRODUCT: TSMXXX-DE09.08

PRODUCT RANGE: 390-405W

405W+


MAXIMUM POWER OUTPUT

0~+5W

BINNING TOLERANCE

21.1%

MAXIMUM EFFICIENCY



Small in size, big on power

- Small form factor. Generate a huge amount of energy even in limited space. Up to 405W, 21.1% module efficiency with high density interconnect technology
- Mono Perc + Multi-busbar technology for better light trapping effect, lower series resistance and improved current collection
- Reduce installation cost with higher power bin and efficiency
- Boost performance in warm weather with lower temperature coefficient (-0.34%) and operating temperature



Universal solution for residential and C&I rooftops


- Designed for compatibility with existing mainstream optimizers, inverters and mounting systems
- Perfect size and low weight. Easy for handling. Economy for transporting
- Diverse installation solutions. Flexible for system deployment



High Reliability

- 15 year product warranty
- 25 year performance warranty with lowest degradation;
- Mechanical performance up to 6000 Pa positive load and 4000 Pa negative load
- Fire Class rating C

Trina Solar's Backsheet Performance Warranty




Comprehensive Products and System Certificates




IEC61215/IEC61730/IEC61701/IEC62716/UL61730
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 ISO45001: Occupational Health and Safety Management System




DIMENSIONS OF PV MODULE(mm)



I-V CURVES OF PV MODULE(400W)



P-V CURVES OF PV MODULE(400W)



ELECTRICAL DATA (STC) TSM-XXXDE09.08(XXX=390-405)

Parameter	390	395	400	405
Peak Power Watts-P _{MAX} (Wp)*	390	395	400	405
Binning Tolerance-P _{MAX} (W)	0 ~ +5			
Maximum Power Voltage-V _{MPP} (V)	33.8	34.0	34.2	34.4
Maximum Power Current-I _{MPP} (A)	11.54	11.62	11.70	11.77
Open Circuit Voltage-V _{OC} (V)	40.8	41.0	41.2	41.4
Short Circuit Current-I _{SC} (A)	12.14	12.21	12.28	12.34
Module Efficiency η _m (%)	20.3	20.5	20.8	21.1

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Parameter	295	298	302	306
Maximum Power-P _{MAX} (Wp)	295	298	302	306
Maximum Power Voltage-V _{MPP} (V)	31.8	32.0	32.2	32.5
Maximum Power Current-I _{MPP} (A)	9.26	9.32	9.38	9.41
Open Circuit Voltage-V _{OC} (V)	38.4	38.6	38.8	38.9
Short Circuit Current-I _{SC} (A)	9.78	9.84	9.90	9.95

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
No. of cells	120 cells
Module Dimensions	1754×1096×30 mm (69.06×43.15×1.18 inches)
Weight	21.0 kg (46.3 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	EVA/POE
Backsheet	White
Frame	30mm(1.18 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: 280/280 mm(11.02/11.02 inches) Landscape: 1100/1100 mm(43.31/43.31 inches) or customized
Connector	Genuine MC4 EVO2 / TS4

TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P _{MAX}	-0.34%/°C
Temperature Coefficient of V _{OC}	-0.25%/°C
Temperature Coefficient of I _{SC}	0.04%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating*	20A / 25A

*Default 20A / 25A upon special request

WARRANTY

15 year Product Workmanship Warranty
 25 year Power Warranty
 2% first year degradation
 0.55% Annual Power Attenuation

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 36 pieces
 Modules per 40' container: 936 pieces